



Technical Specification

Colour Sorter Model : DREAM Series

Model	Working Unit	Power of Main Machine	Voltage	Air Pressure	Air Consumption	Dimension	Weight
ID-360	360 Channels	3.0kw	220V 50Hz	0.6-0.8MPa	<3.0m ³ /min	2710 x 1580 x 2020 mm	1700kg
ID-480	480 Channels	3.6kw	220V 50Hz	0.6-0.8MPa	<4.0m ³ /min	3333 x 1580 x 2020 mm	2070kg
ID-600	600 Channels	4.2kw	220V 50Hz	0.6-0.8MPa	<5.0m ³ /min	3925 x 1580 x 2020 mm	2430kg
ID-780	780 Channels	4.8kw	220V 50Hz	0.6-0.8MPa	<6.5m ³ /min	4445 x 1620 x 2020 mm	3160kg

CONFIGURATION INDEX

Index	Item	DREAM SERIES(Standard)	DREAM SERIES(Luxury)
Performance Index	Key Components	15-inch LCD	●
		Micron-sized HD color sensor	●
		Infrared Imaging System	●
	Sorting Index	Yield per Chute	>2.5t
		Shape Sorting	●
		Spectrum Confocal 2.0 system	●
		Targeted Sorting	●
	Service Life	Patented Maglev Ejector	>10 billion times
		LED	>50 thousand hours
		Power Supply	>50 thousand hours
	Foreign Materials Removal	Glass, desiccants	☆☆☆☆☆
		Plastics	☆☆☆
		Same-in-color stones	—
		Foreign materials	—
	Air Circuit System	Point-to-point Dust Sucking System	●
		High-efficiency Air Circuit System	●
	Machine Protection	Chute Cover	○
		Input Protection Cover	●
Intelligent Index	Intelligent Production Line	Extremely Simplified Interface	●
		Sorter Care 5.0	●
		Remote Commission	●
		Auto-check & Auto-tuning	●
		Automatic backup	●
		Panorama quality analyzer	○

Parameters above are tested on the environment of 25 °C and 2% impurities rate and may change in different conditions.

☆: Function strength, ●: Standard, ○, Selection -: No



ISO 9001 : 2015
Approval No : 0048394

TEL: 604-9178799

FAX: 604-9176799

EMAIL: ipma@ipmaindustry.com

WEB: www.ipmaindustry.com

Address: LOT 1266, BANDAR DARULAMAN INDUSTRIAL PARK, 06000 JITRA, KEDAH DARUL AMAN, MALAYSIA.